



SoySolv® I

Best Applications:

- Asphalt and Tar Removal
- Grease and Oil Cleanup
- Excellent Lubricity Additive
- Adhesive and Decal Removal
- Effective Mold Release
- Excellent Replacement for Mineral Spirits and d-Limonene

Usage and Environmental Benefits:

- Certified by the USDA as a 98% Bio-based product
- Green Verified by the US EPA and Listed on the EPA Safer Chemicals List
- Replaces Traditional Toxic Solvents for Many Cleaning and Degreasing Applications
- Not Proposition 65 Listed
- 100% Biodegradable to Carbon Dioxide and Water
- Available in Jugs, Drums, and Totes

Technical Data:

Dangerous goods	Non-Hazardous	Abrasives:	None
class:			
Physical State:	Liquid	Flash point:	> 300° F Pensky-Marlens closed cup
Odor:	Mild, no fragrance		>650° F open cup
	added		
Color:	Pale yellow	Boiling point:	420° F
PH Concentrate	N/A	Vapor Pressure:	OmmHg
		@72° F	
Net Weight:	7.33 LB/GAL	Evaporation rate:	0.0098
Specific Gravity	0.88	VOC content:	<50g/L
Molecular Weight:	292 grams/mol.	Toxicity;	17.4g/Kg
Solubility in water:	None	Biodegradable:	Yes, begins at 28 days in soil
Rinsability:	None	Surfactants:	None

Warning: To help prevent damage to exterior surface finish, please wipe off and/or rinse with water any residual release agent from all painted surfaces.

CONTACT US: P: 877-769-7658 • F: 440-582-8630 E: sales@soysolv.com Soysolv.com

