

DESCRIPTION

SoySolv AR is a highly effective bio-based asphalt and tar remover, specifically formulated from renewable resources to replace diesel and citrus solvents. Through extensive research and field testing, SoySolv AR is proven to be more efficient and much safer than diesel fuel or citrus based solvents for dissolving asphalt. SoySolv AR's high flash point makes it a safe and highly effective drag slat cleaner that prevents asphalt build up and lubricates drag slat equipment.

KEY BENEFITS

- Economical Pricing – Half the cost of d-limonene products
- Slow Evaporation Rate – Leaves behind slick film preventing future buildup
- High Flash Point
- Environmentally safe solvent - 100% Biodegradable
- Safe and easy to use, non-toxic formulation
- Lab and field tested to outperform diesel and last longer than citrus

USAGE DIRECTIONS

- DO NOT DILUTE
- **TO REMOVE ASPHALT BUILDUP:** Coat tools or equipment to be cleaned with SoySolv AR, then wait 10-20 minutes for SoySolv AR to penetrate the asphalt. For heavy build-up, allow for longer time. SoySolv AR has a low evaporation rate and will continue working even after several hours post application. Use scraper or high water pressure to remove softened asphalt
- **DRAG SLAT CLEANER:** At the end of a production shift, coat drag slats and other equipment to be cleaned with SoySolv AR, then wait 10-20 minutes for SoySolv AR to penetrate the asphalt. For heavy build-up, allow for longer time. SoySolv AR has a low evaporation rate and will continue working even after several hours post application. Use scraper or high water pressure to remove softened asphalt

TECHNICAL DATA

APPEARANCE	Clear to Amber
WEIGHT	7.3 lbs. per gallon
FLASH POINT	> 300F
SHELF LIFE	12 months properly stored
GHS HAZARDS	None
ECOTOXICITY	100% Biodegradable
FREEZE POINT	35 F
WATER SOLUBILITY	None
ODOR	Mild, fatty
US DOT	Ships as non-regulated

PRECAUTIONS

- Wear protective gloves/protective clothing/eye protection. Use PPE as required
- Read and understand the Safety Data Sheet before each use
- Product should be stored above 40° F. Protect from freezing
- Warning: to help prevent damage to painted surfaces, wipe off and/or rinse with water
- **Additional precautions, safety information and first aid are contained in the SDS**

